

SIKA 数字温度表

901-902系列

现场温度显示

范围: -40—+300℃

环境温度: -20—60℃ (表盘)

表盘: 直径80mm卡口, 不锈钢1.4301

电源: 锂电池

寿命: 约10年

循环时间: 3s

双显示: 模拟—刻度盘, 61个刻度
数字 —4位, 7节, 11mm高

防护等级: IP65

精度: ≤1%量程

TYPE 901



TYPE 902



订货选型

订货号 (举例)		48	100	9	2	2	2	0	0	0	0
温度计型号	DiTemp										
垂直	901										
轴向	902										
范围:											
-40 +80℃		48									
0 +120℃	(仅 DiTemp)	12									
0 +200℃		20									
0 +300℃		30									
最大插入管长度 L1:											
100mm ¹⁾			100								
160mm			160								
250mm			250								
400mm			400								
插入管类型:											
无螺纹							1				
联合螺母							4				
可调节头							9				
螺纹类型:											
无								0			
外螺纹可调节头								2			
内螺纹可调节头								3			
固定螺纹连接								4			
螺纹类型 dg:											
无									0		
G1/2									2		
G3/4									3		
M18x1.5									6		
M20x1.5									7		
M24x1.5									8		
M27x2									9		
管/可调节头材料:											
不锈钢 1.4571/无接头										1	
不锈钢 1.4571/接头镀锌金色保护膜										2	
不锈钢 1.4571/接头不锈钢 1.4571										3	
插入管直径:											
直径 d2=8mm										0	
直径 d2=6mm										1	
接线:											
无											0
类型:											
标准型											0
Ex 防暴型											1
FDA 食品型											2
变送输出 4-20mA											3
变送输出 4-20mA, 防暴型											4
报警接触(仅 DiTemp)											5
报警接触, 防暴型(仅 DiTemp)											6
变送输出 0-10 V(仅 DiTemp)											7 0